

Subtlety, sophistication and style

English wall panelling is a symbol of elegance and timeless style that brings a unique character to any interior. It combines aesthetics with functionality, introducing warmth, harmony, and classic simplicity to the space. Rooted in the tradition of English residences for centuries, it now fits just as beautifully into modern interiors.


The classic panelling system consists of only three components: a decorative infill and two framing mouldings, making installation quick and straightforward. Our range includes a complete set of ready-to-use elements that you can freely combine to create custom wall designs and patterns.

Geometric layouts pair beautifully with a wide range of colours — and the panelling **can be painted in any colour** to perfectly match the style of your interior.

It's a fast and elegant way to add depth, texture, and character to a room — without the need for major renovation work.

Application

- enhancing interiors with a sense of prestige and formalitu
- accentuating the elegance of classic furniture
- elevating hallways and staircases with refined wall finishes
- decorating doors and furniture surfaces
- · creating independent decorative wall elements
- protecting walls from damage and dirt
- concealing wall imperfections in a tasteful way



Benefits

- full colour customisation available
- versatile design possibilities
- quick and easy installation
- acoustic and thermal insulation
- durable and low-maintenance
- conceals wall imperfections and irregularities

Component overview

- top mouldings:
 - Flexi. 12x14
 - Morfeusz, 25x22
 - **Elegant**, 22x40
 - **Greta**, 38x44
 - **Aura**, 19x60
- infill panels:
 - Wainscoting **OXFORD**
 - Wainscoting ELBY
- skirting boards:
 - **D2**, 15x150x2400
 - **D8**. 15x150x2400
 - **D11**, 15x150x2400
 - **D16**, 15×120×2400





The product should be protected from moisture, it is adapted for installation indoors only; store in dry and closed places in a horizontal position, away from heat sources, at temperatures up to 50°C, with a maximum humidity of 60%. Do not use mounting adhesives containing solvents.





Mixpol Profile sp. z o.o. ul. Parkowa 4 47-330 Zdzieszowice, Poland



+48 77 472 61 65 www.mixpolprofile.pl