

Cover strips and corners

Product Data Sheet (PDS)

last modified: 2025.06.13



1. Product Characteristics

→ **Cover strips and corners** are made of MDF covered with decorative foil. A hot-melt adhesive is used for lamination.

2. Material Composition

MDF board, pre-impregnated decorative foil, hot-melt adhesive

3. Technical Parameters

• width tolerances [mm]	±1.0
• height tolerance [mm]:	±1.0
• length tolerance [mm]:	
• cover strip	+5/-0
• corners	±1.0
• density of the MDF board [kg/m ³]:	600-800
• perpendicular cutting tolerance [°]	±0.5
• product thermal resistance [°C]	max 50

→ [Technical Drawing of type D3](#)

→ [Technical Drawing of type D8](#)

4. Application/Functionality

concealing pipes, cables, curtain rods, etc.; interior decoration

5. Assembly Method:

installation can be carried out with assembly adhesive or wall plugs; **WARNING:** in case of adhesive installation, do not use solvent-based adhesives; at least 24 hours before final installation, a test bonding should be carried out to check the strength of the bond and ensure that the chosen adhesive does not cause damage to the product

6. Storage and Transportation

store in original, undamaged packaging, in dry and covered areas only (maximum temperature: 50°C; maximum humidity: 60%), in a horizontal position on flat surfaces to prevent bending or deformation; protect from moisture and direct sunlight

7. Usage Recommendations

do not use chemical agents to remove dirt or stains; intended for indoor use only; protect from moisture and temperatures exceeding 50°C; when securing the product (e.g. during renovation or painting), use only standard painter's tape, which should be removed within 24 hours

8. Safety Instructions

this product is not a toy; assembly should be carried out only by adults or under adult supervision

TAKE EXTRA CARE:

- installation requires the use of tools and materials that may pose a risk of injury
- during installation, there is a risk of contact with small parts that may cause choking or suffocation (e.g. product offcuts)
- the product may have sharp edges and corners
- during use, extra caution should be exercised in the presence of children and/or persons with disabilities to prevent hazardous situations or unsafe behavior
- a safe distance must be maintained between the product and heat sources (such as radiators, fireplaces, stoves, etc.)
- waste generated after using the product should be sorted and disposed of at selective collection points, in accordance with local regulations

9. Interaction with Other Products

not applicable

10. Impact of Other Products on the Item

do not use chemical agents to clean dirt; maintain a safe distance between the product and heat sources (radiators, fireplaces, stoves, etc.); do not use mounting adhesives containing solvents for fixing the product; when securing the product (e.g. during renovation or painting), use only standard painter's tape, which should be removed within 24 hours

11. Additional information

MDF is hygroscopic, which may cause the material to expand in response to moisture. The material is prone to warping, resulting in deviations from straightness. These natural material characteristics are not considered product defects. **Formaldehyde emission: Class E05, E1.**

The products covered by this PDS comply with European Regulation **REACH No. 1907/2006** and do not contain substances listed as SVHC (Substances of Very High Concern) candidates; the products **are not construction products** and are not subject to the **directive 305/2011**.